

STEK[®] Paint Protection Film Technical Data Sheet



CHARACTERISTICS

- Matte finish
- Water-repellent
- Anti-yellowing
- Anti-contamination

APPLICATIONS

For automotive use
(other uses may apply).

APPLICATION AREAS

Flat surfaces, simple curves,
and compound curves

APPLICATION METHOD

Paint protection films are to be
professionally installed by trained,
authorized installers.

SHELF LIFE

Paint protection films should be
installed within one year from the
date of purchase.

LAYER DESCRIPTIONS

Top Coat (Matte)

Provides matte finish

TPU

High-clarity and impact-resistant

Pressure-Sensitive Adhesive (PSA)

For easy installation

Release Liner

Protects film before use

LAYER THICKNESS

145 ± 10 µm

PRODUCT DESCRIPTION


MATTE effect is a cost-efficient paint protection film suitable for a wide variety of vehicle types. Our unique film adds a stylish matte finish to any original paint color, creating an eye-catching, modernizing effect. High-clarity and anti-yellowing, MATTE effect works to preserve gloss while guarding against environmental contamination. Compared to vinyl films, which are extremely susceptible to orange peeling and other types of deterioration, our TPU film features significantly higher damage resistance—offering better, longer-lasting protection.

STORAGE INSTRUCTIONS

Recommended Temperature Range: 20±2 °C (68±2 °F)
Recommended Relative Humidity: 40-60%

Avoid extreme temperature ranges in storage. Store the product in its original packaging in a horizontal orientation, away from direct sunlight. Do not place heavy objects on top of the packaging, as this may damage the product.

STRUCTURE



PROPERTIES

Gloss	<19 Gu
Self-Healing	Standard
Coating Layer Crack	>60 mm
Adhesion (30 min.)	>1200
Adhesion (24 hrs)	>1500
Hydrophobicity	Water-repellent
Weathering	No change 6500 W Xenon Arc Irradiance: 0.51 W/m ² (340 nm), 65° C Humidity: 50%, R.H. 1000 hrs

STEK® Paint Protection Film
Technical Data Sheet

**PACKAGE
DIMENSIONS**

Box Size
1630 x 185 x 180 (mm)

ROLL CONFIGURATIONS

60 in. x 66 ft (1524 mm x 20 m)

NOTES

All data have been collected by STEK Automotive through internal testing standards and methods. Results may differ when using other testing standards.

Reported values are expected properties and should not be used for product certification.

The provided technical information consists of representative product data and should not be used for specification purposes. Unless otherwise noted, all tests are performed at room temperature.

All concerns regarding warranty and liability are subject to the terms and conditions of sale. When applicable, these terms and conditions are governed by prevailing laws.

Prior to application, the user must determine the suitability of the product for its intended use, and assumes all risk and liability therein.

WARRANTY

5-year limited warranty

Only applicable in the case of proper handling and use. Terms and conditions apply.